

製品名	27インチ IP65 防水モニター (アルミフレーム)
LCD パネル	
IP レベル	IP65 (全面)
アクティブスクリーンサイズ(cm) :	597.6(W)×336.15(H) mm
解像度 :	1920*1080
カラー	16.7M
輝度(cd/m ²)	300cd
コントラスト	3000:1
視野角 水平/垂直(°)	89/89/89/89
バックライト種類/バックライト寿命(時間)	LED/40,000
タッチパネル	
タッチ方式	静電容量
タッチ接続方式	USB
操作/機械仕様	
動作温度(°C)	-10~60
湿度範囲	10%-90%
製品重量(kg)	12
フレーム材料	アルミニウム
フレーム寸法(cm)D*W*H	660 x 398.2 x 64.5mm
取り付け方法	VESA100*100
電気供給	
消費電力(W)	25
電源	DC12V
外部コネクタ	
1x VGA	
1x HDMI	
1x USB-Touch	
1x 電源アダプター	
図面	
<p>The technical drawing illustrates the monitor's dimensions and mounting specifications. The front view shows an outer frame of 660 mm width and 398.2 mm height, with an inner active display area of 597.6 mm width and 336.15 mm height. The side view indicates a thickness of 64.5 mm. The rear view details the VESA 100x100 mm mounting bracket with four 4-ø5 mm mounting holes. The distance between the mounting holes is 100 mm horizontally and 100 mm vertically. The distance from the center of the mounting holes to the edges of the frame is 74 mm horizontally and 77.6 mm vertically. The distance from the center of the mounting holes to the center of the display is 200 mm horizontally and 91.5 mm vertically. The distance from the center of the mounting holes to the bottom edge of the frame is 81.5 mm. The distance from the center of the mounting holes to the top edge of the frame is 81.5 mm. The distance from the center of the mounting holes to the left edge of the frame is 156 mm. The distance from the center of the mounting holes to the right edge of the frame is 156 mm. The distance from the center of the mounting holes to the bottom edge of the display is 81.5 mm. The distance from the center of the mounting holes to the top edge of the display is 81.5 mm. The distance from the center of the mounting holes to the left edge of the display is 156 mm. The distance from the center of the mounting holes to the right edge of the display is 156 mm.</p>	